


PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification 5 : G01R 33/44</p>	<p>A1</p>	<p>(11) International Publication Number: WO 93/11441 (43) International Publication Date: 10 June 1993 (10.06.93)</p>
<p>(21) International Application Number: PCT/GB92/02254 (22) International Filing Date: 4 December 1992 (04.12.92) (30) Priority data: 9125883.0 5 December 1991 (05.12.91) GB (71) Applicant (for all designated States except US): BRITISH TECHNOLOGY GROUP LIMITED [GB/GB]; 101 Newington Causeway, London SE1 6BU (GB). (72) Inventors; and (75) Inventors/Applicants (for US only) : SMITH, John, Alec, Sydney [GB/GB]; 28 Leeward Gardens, London SW19 7QR (GB). SHAW, Julian, David [GB/US]; 618 San Dieguito Drive, Encinitas, CA 92024 (US).</p>		<p>(74) Agent: COZENS, Paul, Dennis; Mathys & Squire, 10 Fleet Street, London EC4Y 1AY (GB). (81) Designated States: JP, RU, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i></p>

(54) Title: IMPROVEMENTS IN NQR TESTING



(57) Abstract

A method of Nuclear Quadrupole Resonance testing includes the steps of applying to a sample in which selected nuclei have an integral spin quantum number a series of at least three pulses of electromagnetic waves at a single radiofrequency to excite quadrupole resonance of the selected nuclei (waveform (a)), and detecting responses at a plurality of times when echo response signals are expected to occur (waveform (b)).

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

WO 93/11441

PCT/GB92/02254

- 1 -

IMPROVEMENTS IN NQR TESTING

The present invention relates to a method of nuclear quadrupole resonance (NQR) testing of integral spin quantum
5 number spin systems.

NQR testing is used for detecting the presence or disposition of specific substances. It depends on the energy levels of quadrupolar nuclei, which have a spin quantum number greater than one-half. Quadrupolar nuclei having an integral
10 spin quantum number (that is, $I = 1, 2, 3 \dots$) include ^{14}N ($I=1$). ^{14}N nuclei are present in a wide range of substances, including animal tissue, bone, food-stuffs, explosives and drugs.

In the sub-molecular environment of compounds or crystals, the nature and disposition of the electrons and atomic nuclei
15 produce an electric field gradient which modifies the nuclear energy levels to such an extent that measurements of NQR effects can indicate not merely the nuclei which are present but also their chemical environment, thus indicating specific substances or types of substances in any tested sample.

In NQR testing a sample is irradiated with pulses or sequences of pulses of radiofrequency electromagnetic waves having a frequency which is at or very close to a resonant
20 frequency of quadrupolar nuclei in a substance which is to be detected. If the substance is present, the irradiant energy will raise at least some of the nuclei to a higher energy
25 level. Such nuclei will tend to return to their normal state and in doing so they will emit radiation at their resonance frequency or frequencies which can be detected as a free induction decay (f.i.d.) during a decay period after each
30 pulse. These emissions decay at a rate which depends on two relaxation time constants, T_1 and T_2 .

In conventional NQR testing, either a substantial part of the free induction decay is measured after each pulse or the responses are measured as echoes in relatively short sampling
35 periods between or following a relatively rapid succession of

WO 93/11441

PCT/GB92/02254

- 2 -

pulses. Usually the results from a number of test pulses or test sequences are integrated to improve the signal-to-noise ratio. Various schemes of pulse sequences have been used.

In a scientific paper by Grechiskin et al. (Adv. N.Q.R., 1983, 5, 1) it has been predicted theoretically that conditions might arise which could give rise to the formation of a single echo as well as a free induction decay from nuclei of unity spin quantum number when excited by two excitation pulses at a single radiofrequency. No details are given as to how, or even whether, this can be achieved experimentally.

In a paper by Bloom et al. (Physical Review 1955, vol. 97, 1699) it has been reported that multiple echoes as well as a free induction decay have been observed in tests from nuclei of spin quantum number $3/2$ in a weak magnetic field. The paper demonstrates that the magnetic field removes degeneracies which would otherwise so broaden and attenuate the echoes that no useful NQR information would be yielded. However, this technique would not be expected to work for integral spin systems, since such systems are not strongly affected by a weak applied magnetic field.

According to the present invention, a method of NQR testing includes the steps of applying to a sample in which selected nuclei have an integral spin quantum number a series of at least three pulses of electromagnetic waves at a single radiofrequency to excite quadrupole resonance of the selected nuclei and detecting responses at a plurality of times when echo response signals are expected to occur.

We have found that, surprisingly, for samples in which the selected nuclei have an integral (e.g. unity) spin quantum number, in addition to the free induction decay which occurs immediately after a single frequency excitation pulse, there are some substantial NQR echo responses which occur after delays matching the time intervals between preceding pulses. It has been found that, if time τ is measured from the first pulse of a series of pulses of pre-selected widths and phases occurring at

WO 93/11441

PCT/GB92/02254

- 3 -

times 0, τ_1 , τ_2 τ_N which are not necessarily identically spaced there are substantial echo responses at many, although not all of, the following times:

$$\begin{aligned} & \tau_n + \tau_n = 2\tau_n \\ 5 \quad & \tau_n + (\tau_n - \tau_1) = 2\tau_n - \tau_1 \\ & \dots\dots\dots \\ & \tau_n + (\tau_n - \tau_{n-1}) = 2\tau_n - \tau_{n-1} \end{aligned}$$

where $n = 1$ to N . It has also been found that there can be echo responses which occur after a delay which matches the time interval between an excitation pulse and a echo response which precedes it, for instance at times

$$\tau_n + (\tau_n - 2\tau_1) = 2\tau_n - 2\tau_1.$$

The times when echo response signals would be expected to occur for a particular substance or class of substance can be predetermined by experimentation in a manner which will be evident to a person skilled in the art.

It will be appreciated that, since more (often many more) echoes may be detected from the sample than excitation pulses are applied to the sample, and since the usual f.i.d.'s may also be detected, a larger signal-to-noise ratio can be obtained than would be obtained for a system in which a multiple echo train was not generated; the sensitivity of the tests can thus be improved. Therefore, it is preferred that the responses to the excitation pulses are summed.

For simplicity and economy, it is preferred that the application and detection steps take place in the absence of an applied magnetic field.

Preferably, the interval between the first and second pulses of the series is different from the interval between the second and third pulses. It has now been discovered that, using such intervals, stimulated NQR echoes can be generated, with the attendant possibility of there being more echoes generated and detected than there are pulses applied. This can in turn afford the advantage of larger signal-to-noise ratio and increased sensitivity mentioned previously.

WO 93/11441

PCT/GB92/02254

- 4 -

The pulse times τ_n are preferably chosen to have no common factor and so that the echo times are distinct and separated from the excitation pulse times. Preferably $\tau_n > 2\tau_{n-1}$ and in some cases it may be necessary to have the condition $2\tau_n < T_1$ where T_1 is the spin-lattice relaxation time for the resonance being tested. The time intervals $(\tau_n - \tau_{n-1})$ may be greater than those used in conventional NQR test pulse sequences; usually $(\tau_n - \tau_{n-1}) > T_2^*$, where T_2^* is the f.i.d. time.

In a preferred embodiment, the pulses of the series are applied at times 0, τ_1 and τ_2 and the echo response signals are measured in periods embracing at least some of the times $2\tau_1$, $\tau_1 + \tau_2$, $2\tau_2$ and $2\tau_2 - 2\tau_1$. It is also preferred that $\tau_2 > 2\tau_1$ and τ_1 and τ_2 have values which make the times τ_1 , τ_2 , $2\tau_1$, $\tau_1 + \tau_2$, $2\tau_2 - 2\tau_1$ and $2\tau_2$ separate and distinct from one another.

If pulses are applied to the sample at times 0, τ_1 and τ_2 , it has been found that there may be little or no substantial echo response at time $2\tau_2 - \tau_1$ for integral spin quantum number systems. This fact can be used effectively to perpetuate or at least prolong the echo train. A further excitation pulse may be applied at time $2\tau_2 - \tau_1$. This will produce further echoes without suppressing or affecting the quality of detectable NQR information. Additional pulses may be applied at some or all of times $(2\tau_n - \tau_{n-1})$ ($n = 3, 4, 5, \dots$) to further prolong the multiple echo train. There may be times other than $(2\tau_n - \tau_{n-1})$ when there are no substantial echo responses. In this case, the further excitation pulses could be applied at these times additionally or instead.

Preferred features of the invention will now be described with reference to the accompanying drawings, in which:-

Figure 1 is a block circuit diagram of apparatus for NQR testing; and

Figure 2 is a graphical diagram showing response signals detected in a test with the apparatus of Figure 1.

In Figure 1 a radiofrequency source 10 is connected to an rf power amplifier 11. The output of rf amplifier 11 is connected

WO 93/11441

PCT/GB92/02254

- 5 -

through switching and timing circuits 12 to r.f. coils 13 which are disposed about the sample to be tested (not shown). The switching and timing circuits 12 also connect the coils 13 to a detecting and measuring circuit 14, which is also connected to a graphical recorder 15. The switching and timing circuits 12 also control the timing and phase of the signals applied by the r.f. source 10 to the r.f. power amplifier 11. It will be appreciated that numerous modifications to the apparatus described are possible, as will be apparent to the skilled person.

In Figure 2 waveform (a) represents the excitation pulse control signals applied to control a series of three single frequency excitation pulses, and waveform (b) represents the graphical recorder trace of detected NQR responses. A time scale is shown below this trace. As shown, the excitation pulses occurred at times $\tau = 0, 2.5 \text{ ms } (\tau_1)$ and $9.5 \text{ ms } (\tau_2)$. The pulse sequence was of the form $90^\circ_0 - \tau_1 - 90^\circ_0 - \tau_2 - 90^\circ_0 -$. Each excitation pulse lasted for $20 \mu\text{s}$ and was followed by a blanking period of $200 \mu\text{s}$; during these times the detecting circuit was not connected to the coils, to avoid overload. In this particular test the single radiofrequency f_0 of the excitation pulses (5307 kHz) was slightly offset from one of the resonance frequencies $f_r = 5302 \text{ kHz}$ of ^{14}N nuclei in the sample, which was a sample quantity of the explosive HMX at a temperature close to 298 K . This produces a response showing variations at the beat frequency $f_0 - f_r$. The trace clearly shows the NQR echo responses occurring around the times $2\tau_1, \tau_2 + \tau_1, 2\tau_2 - 2\tau_1$, and $2\tau_2$. A possible response at $2\tau_2 - \tau_1$ is either very weak or is thought perhaps not to exist at all. Parts 20 and 21 of the trace show the f.i.d.s after the first and third excitation pulses; the f.i.d. after the second pulse does not appear on this trace which shows the output of only one of two channels arranged to measure signals of opposite phase. The excitation signals in the second pulse may be in antiphase relationship with the signals of the first and third pulses.

WO 93/11441

PCT/GB92/02254

- 6 -

From this trace it is clear that the three pulses generate at least four substantial echo response signals which in this instance are comparable with the largest measurable f.i.d. It will be noted that each of the echo responses is spread over a period of about 1 millisecond which is about twice the f.i.d. time constant T_2^* and is fifty times longer than the excitation pulse length. The strength and duration of the echo responses are so great that by using them in addition to the f.i.d.'s the sensitivity of the tests can be greatly increased.

WO 93/11441

PCT/GB92/02254

- 7 -

CLAIMS

1. A method of NQR testing which includes the steps of applying to a sample in which selected nuclei have an integral spin quantum number a series of at least three pulses of
5 electromagnetic waves at a single radiofrequency to excite quadrupole resonance of the selected nuclei and detecting responses at a plurality of times when echo response signals are expected to occur.
2. A method as claimed in Claim 1 and wherein the responses to
10 the excitation pulses are summed.
3. A method as claimed in Claim 1 or 2 and wherein the application and detection steps take place in the absence of an applied magnetic field.
4. A method as claimed in Claim 1, 2 or 3 and wherein the
15 interval between the first and second pulses of the series is different from the interval between the second and third pulses.
5. A method as claimed in Claim 1, 2, 3 or 4 and wherein the pulses of the series are applied at times 0, τ_1 and τ_2 and the echo response signals are measured in periods embracing at least
20 some of the times $2\tau_1$, $\tau_1 + \tau_2$, $2\tau_2$ and $2\tau_2 - 2\tau_1$.
6. A method as claimed in Claim 5 and wherein $\tau_2 > 2\tau_1$ and τ_1 and τ_2 have values which make the times τ_1 , τ_2 , $2\tau_1$, $\tau_1 + \tau_2$, $2\tau_2 - 2\tau_1$ and $2\tau_2$ separate and distinct from one another.
7. A method as claimed in Claim 5 or Claim 6 and wherein τ_1 is
25 greater than one millisecond.
8. A method as claimed in any of the preceding claims and wherein the pulses of the series are applied at times τ_n , where $n = 0$ to N and N is greater than or equal to two, at least one of the pulses in the series being applied at a respective time
30 $2\tau_n - \tau_{n-1}$ (n greater than one).
9. A method as claimed in any of Claims 5 to 7 and wherein a further pulse in the series is applied at time $2\tau_2 - \tau_1$ or $2\tau_n - \tau_{n-1}$ in general.
10. A method of NQR testing substantially as herein described
35 with reference to the accompanying drawings.

PCT

WO 93/11441

PCT/GB92/02254

1/2




Fig. 1

WO 93/11441

PCT/GB92/02254

2/2




Fig. 2

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 92/02254

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
Int.Cl. 5 G01R33/44		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int.Cl. 5	G01R ; G01V ; G01N	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ⁹	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
A	INSTRUMENTS AND EXPERIMENTAL TECHNIQUES. vol. 28, no. 2, 1 March 1985, NEW YORK US pages 426 - 428 A.A. BOGUSLAVSKII ET AL. 'AUTOMATIC NUCLEAR-QUADRUPOLE-RESONANCE MEASUREMENTS USING AN ELEKTRONIKA D3-28 MICROCOMPUTER' see the whole document ---	1-3
A	ELECTRO CONFERENCE RECORD vol. 4, 24 April 1979, LOS ANGELES US pages 1841 - 1845 J.R. GONANO 'NUCLEAR MAGNETIC RESONANCE AND NUCLEAR QUADRUPOLE RESONANCE FOR BOMB DETECTION' see the whole document --- -/-	1-3
<p>⁹ Special categories of cited documents : ¹⁰</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search 03 MARCH 1993		Date of Mailing of this International Search Report 08 MAR 1993
International Searching Authority EUROPEAN PATENT OFFICE		Signature of Authorized Officer HORAK G.I.

GB 9202254
SA 67347

03/03/93

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB-A-2200462	03-08-88	EP-A- 0277745	10-08-88
		JP-A- 63259449	26-10-88
		US-A- 4887034	12-12-89

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.